

OPEN STANDPIPE PIEZOMETER

Model EPP-10SP

DATASHEET



OVERVIEW

The Encardio Rite model EPP-10SP Open Standpipe Piezometer is designed for simple and accurate measurement of groundwater levels and its variation with time in boreholes and wells. It is particularly useful for monitoring groundwater tables near dams, rivers, high-rise buildings, farmhouses, factories, and residential areas. The piezometer is ideal for applications where reliable and cost-effective groundwater level monitoring is required.

The EPP-10SP Open Standpipe Piezometer consists of a series of PVC standpipes and a slotted pipe covered with geo-textile at the bottom. Once installed in the borehole of desired depth, the groundwater seeps into the standpipe through the slotted end and attains a level equal to surrounding groundwater table. The level of water in the riser pipe is determined by the graduated water level sounder lowered from the ground surface, giving an accurate reading of surrounding pore pressure. The device's simplicity and reliability make it ideal for long-term monitoring.

FEATURES

- **Reliable and rugged:** The piezometer is built for durability, making it suitable for long-term monitoring in various environments.
- **Simple and economical:** Easy to install and maintain, providing an economical solution for groundwater monitoring.
- **Portable water level sounder:** The water level sounder is lightweight and easy to carry, with a flat cable that is high tensile, virtually non-expandable, waterproof, and corrosion-resistant.
- **Accurate:** Provides precise groundwater level measurement with a high-resolution graduated tape.
- **Easy to read:** Easy-to-read audio and visual signals.
- **Heavy duty construction:** Standpipe constructed from durable PVC to withstand harsh environmental conditions.
- **Locking arrangement:** A locking cover with a universal key is provided to protect the standpipe from external contamination.

SYSTEM COMPONENTS


Slotted pipe: It consists of PVC slotted pipe covered with geo-textile material, to allow water flow while preventing debris entry. It is available in 1 m lengths as standard. 2 m or 3 m lengths are also available on request. Bottom end of slotted pipe is plugged with a suitable PVC cap.

Standpipe: It consists of durable rigid PVC pipe, 3 m long. The pipe features inbuilt socket for jointing, allowing for longer installations by connecting multiple tubes together using an appropriate adhesive or resin.

Top cap: It is attached to the upper end of the topmost standpipe.

MS lockable protective manhole cover: It is available on request, to safeguard the installation from moving vehicles and other potential site damage.

Water Level Sounder (Model EPP-10/6): A robust, lightweight device used to measure the groundwater level in the standpipe. The sounder consists of a probe connected to a flat cable with high-tensile steel tape, providing both audio and visual signals when water is detected.



Typical installation scheme of EPP-10SP Open Standpipe

SPECIFICATIONS

EPP-10SP Open standpipe piezometer

Porous tip	PVC slotted pipe, 50 mm o.d., 1 m long, covered with geo-textile. 2 m, 3 m lengths available on request.
------------	--

Standpipe	50 mm o.d., 44.5 i.d., 3 m length PVC pipe with an inbuilt socket for jointing
-----------	--

EPP-10/6 Water level sounder

Length-metric (m)	30, 50, 100, 150, 200, 300
-------------------	----------------------------

Resolution-metric	1 mm standard
-------------------	---------------

Length-imperial (ft)	50, 100, 150, 300, 500
----------------------	------------------------

Resolution-imperial	0.1" standard
---------------------	---------------

Cable/tape	High tensile virtually non-expandable, non-stretch, PE insulated graduated flat steel tape 10 mm wide x 2 mm thick
------------	--

Probe	Stainless steel 12.7 mm dia.
-------	------------------------------

Power supply	9 V PP-3 size battery
--------------	-----------------------

Audio signal	Sound buzzer
--------------	--------------

Visual signal	Green LED light signal
---------------	------------------------

Please refer to datasheet for EPP-10/6 water level sounder for more details.

ORDERING INFORMATION

- Length of casagrande tip.
- Depth of borehole (for riser pipe estimation).
- Manhole cover required or not.
- Length ad unit for water level sounder.

Ordering code

EPP-10SP-L-Y [L= length of slotted pipe, Y= No. of standpipes]

EPP-10/6-L-X [L= length, X = unit (m or ft)]

*All specifications are subject to change without prior notice

DATASHEET | 1038-12 R03



Dams



Mining



Tunnels



Transportation



Construction



Bridges



Landslides



Energy



Environmental
Monitoring



Pipelines



Structural Health
Monitoring



Smart
Cities

ENCARDIO RITE GROUP - INDIA | BHUTAN | NEPAL | BAHRAIN | QATAR | SAUDI ARABIA | UAE | PERU | GREECE | SPAIN | UK | USA

Encardio-Rite Electronics Pvt. Ltd. A-7, Industrial Estate, Talkatora Road, Lucknow, UP-226011, India | info@encardio.com | T: +91 522 2661039-320